

Bohrloch	von (m)	bis (m)	Bohrlochlänge (m)	Kupfer (%)	Molybdän (%)
ANT-34	60	82	22	0.55	0.038
ANT-35	38	52	14	0.36	0.001
ANT-36	30	54	24	0.54	0.017
ANT-37	62	142	80	0.52	0.001
	einschl.66	94	28	0.62	0.001
	einschl.118	142	24	0.67	0.001
ANT-38	34	130	96	0.72	0.029
	einschl.34	112	78	0.80	0.029
	einschl.122	130	8	0.63	0.037
ANT-39	2	82	80	0.55	0.002
	einschl.6	26	20	0.60	0.001
	einschl.36	82	46	0.61	0.002
ANT-40	14	84	70	0.48	0.008
	einschl.14	36	22	0.62	0.005
	einschl.56	70	14	0.68	0.013
	einschl.76	84	8	0.58	0.018
ANT-41	58	149	91	0.56	0.013
	einschl.74	149	75	0.60	0.014
	einschl.114	149	35	0.73	0.018
ANT-42	34	44	10	0.68	0.004
	114	121	7	0.53	0.002
ANT-43	44	64	20	0.63	0.011
ANT-44	28	36	8	1.10	0.008
	70	90	20	0.56	0.009
	112	119	7	0.34	0.059
ANT-47	86	114	28	0.35	0.014
	138	148	10	0.33	0.012
ANT-50	150	182	32	0.41	0.016
	einschl.168	174	6	0.71	0.024
ANT-51	66	82	16	0.56	0.016
	88	98	10	0.54	0.019
ANT-54	136	156	20	0.64	0.021